

# TOPCRET

The Experts Choice

**CREATE SEAMLESS  
CONTINUOUS SURFACES  
WITHOUT DEMOLITION.**

## **MICROCEMENTO®**



### **SEAMLESS**

Microcemento® creates unique and jointless spaces. Due to his excellent adherence, it can be applied on almost all surfaces.



### **SUSTAINABLE**

It is ideal for renovation projects since it does not require removing existing material or adjusting the floor levels.



### **HANDCRAFTED**

Available in a wide color palette, textures, and handcrafted trowel finish, Microcemento® achieves surfaces of great quality and beauty.

## Microcemento® has been the micro-coating benchmark since it's launch

- Sustainability is one of Microcemento's key features.  
You can renovate a space without demolition or change in floor height levels because it can be installed directly on top of almost all surfaces.
- We know that time is crucial, that's why Microcemento® is open to foot traffic after 24hs.
- It is totally waterproof, suitable for outdoor, indoor, kitchens, bathrooms, and any wet area.
- Color is one of the most important decisions.  
Microcemento® is not limited to a standard palette. Its coloration system allows you to create an infinite number of color combinations.
- Suitable for walls, ceilings and staircases.

## Combine it with other products

- Summery, integrated heating system
  - Thin, only 3mm. thick.
  - Safe low voltage (24v) and totally waterproof.
  - Uses up to 50% less energy than conventional electric heating systems.
- T/Grip, certified anti-slippery treatment
  - Meets the EU standards (Class 2 & 3).
  - Creates a safer surface (stairs, swimming pools, outdoor patios, etc.).

## Microcemento® textures



## LAB TESTS AND CERTIFICATIONS



Microcemento® has been thoroughly tested by third party entities under international standards, giving us the authority to support our claims.

In the link you will find the last certifications.

## COLORS COLLECTION



	ADHESION RESISTANCE, UNE-EN 13892-6	>1,2 N/MM2
	SURFACE HARDNESS, UNE-EN 13892-6:2003	43 N/MM2
	SLIP RESISTANCE, UNE-ENV 12633 27	27
	ARTIFICIAL AGEING, UNE-EN 1062-11 (500 hours) Cycle: 4 hours UV (60±3) °C / 4 hours humidity (50±3) °C	NO COLOR CHANGE

	WEAR RESISTANCE BCA, UNE-EN 13892 - 4	160 µM
	IMPACT RESISTANCE, UNE-EN ISO 6272	>14,7 N/M



RESISTANCE TO STRONG CHEMICAL ATTACKS, UNE-EN 13529:205

No defects after 7 days of contact for olive oil, water, alcohol, coffee and lye. No defects after 1 day of contact for hair dye and alcohol vinegar. No defects after 6 hours of contact for lemon juice.

london@topcret.com  
Phone: +44 (0) 20 7624 2180

Office & Showroom:  
4 Hampstead West  
224 Iverson Rd, London NW6 2HL  
LONDON - UK

info@topcret.com  
T. +34 932 74 12 08

Oficina Central TOPCRET:  
Gran Via de les Corts Catalanes,  
828, 08013 BARCELONA  
ESPAÑA

# TOPCRET



Management System  
ISO 45001:2018  
ISO 14001:2015  
ISO 9001:2015  
www.tuv.com  
ID 3108635825

